



Architecture 100




FIG. 1

2/14





FIG. 2

3/14

Computer System 300




FIG. 3

4/14




FIG. 4




FIG. 5

FIG. 4

5/14

600

Determine Distance of Scene  
 Pixels from Reference Point




FIG. 6

Linear Fog Equation

Equation One (1)

$$\text{Attenuation Factor}(f) = \frac{\text{Maximum Distance} - \text{Pixel Distance}}{\text{Maximum Distance} - \text{Minimum Distance}}$$

Equation Two (2)

$$\text{Color} = f \cdot \text{Object Color} + (1-f) \cdot \text{Fog Color}$$

Equation Three (3)

$$\text{Color} = \frac{\text{Pixel Distance} - \text{Minimum Distance}}{\text{Maximum Distance} - \text{Minimum Distance}} \cdot \text{Fog Scale}$$

FIG. 7

6/14

Reset Pixel Colors Located Outside the Fog Region




FIG. 8

7/14

Determine Travel Distance through Fog  
Region from Reference Point to Pixel




FIG. 9





FIG. 10

$$\text{Unfogged pixel color} \cdot \text{fog factor} + \text{fog color} \cdot (1 - \text{fog factor})$$
[illegible][illegible]

9/14




FIG. 13A

SECRET 58006660

10/14




FIG. 13B

Patent 5800660

11/14





FIG. 13C

10/22/2014 10:00:00 AM

12/14



Patent 3,800,000






FIG. 13D

13/14



Step 4: convert pixel values



P1 color:  $P1 \text{ color} * \text{fogDensity} / \text{fogScale} * |M1, Z1|$

P2 color:  $P2 \text{ color} * \text{fogDensity} / \text{fogScale} * |M2, Z2|$  note  $|M1, Z1| = |M2, Z2|$   
(linear fog)

or

P1 color:  $\text{pixelmap}[P1 \text{ color} / \text{fogScale} * |M1, Z1|]$

P2 color:  $\text{pixelmap}[P2 \text{ color} / \text{fogScale} * |M2, Z2|]$   
(exp or exp2 fog)

FIG. 13E

14/14




FIG. 13F




FIG. 13F